



AC 1900

Wireless Gigabit VDSL/ADSL Modem Router Archer VR900

Highlights

- Versatile Connectivity Ethernet WAN and USB ports, the VR900 is fully compatible with VDSL2/ADSL2+/ADSL2/ADSL standard, fiber/cable access and 3G/4G USB dongles
- Superfast Wi-Fi 600Mbps on 2.4GHz + 1300Mbps on 5GHz
- · Maximum Range High power amplifiers and 3 dual band detachable antennas provide maximum Omni-directional wireless coverage and reliability
- · 1GHz Dual-core Processor Ensures no interruption while processing multiple wired or wireless tasks simultaneously
- Beamforming Technology Improves wireless range and performancee on both 2.4GHz and 5GHz band















1 GHz CPU

Beamforming Technology

Connection

Guest Network

Parental

Connection

Tether App

Features



Speed

- Blazing Fast Wireless Speed Combined wireless speeds up to 1.9Gbps at 2.4GHz & 5GHz band concurrently
- Support 802.11 ac Offering 3 times faster data rate than 802.11n in a single stream
- Dual-core Processor 1GHz dual-core processor boosts data transfer rate
- Gigabit Wired Speed Full shielded gigabit ports ensure ultrafast data transfer speeds



Wi-Fi Range

- Ultimate Range & Reliable Wi-Fi –
 High-powered amplifiers ensure continuous
 Wi-Fi signal to all your devices while boosting
 widespread converage throughout your very
 large home
- 3 Dual Band Antennas 3 dual band detachable antennas provide maximum Omni-directional wireless coverage
- Beamforming Technology Archer VR900's beamforming technology extends wireless coverage by boosting signal strength



Uses

- DSL Port For VDSL2/ADSL2+/ADSL2/ADSL connections
- Ethernet WAN Port Allows for fiber or cable access
- USB Ports Allows for 3G/4G USB dongle connections
- Easy Setup and Use Provides quick & hassle-free installation and easy management with new web UI and Tether App
- Fast Encryption Easy one-touch WPA wireless security encryption with the WPS button

Features



Reliability

- Simultaneous Dual Band Reduces interference for more stable connections
- Easy Bandwidth Management Bandwidth Control makes it easier for you to manage the bandwidth of connected devices



Easy Sharing

- **10x Faster Transfer Speed** The USB 3.0 port provides up to 10x faster USB hard drive access than earlier USB 2.0 connections
- Dual USB Ports for Fast Sharing With 2 USB 3.0 ports, you can access and share a printer as well as your files and media locally. Via the router's FTP server, you can also have access to your files & media with networked devices remotely
- Built-in Print Server Supports wireless printing from multiple computers (works in conjunction with a USB Printer)
- Built-in Media Server Allows users to play music, video and view photos




Security

- Guest Network Access Guest Network Access provides secure Wi-Fi access for guests
- Parental Control Establish restricted access policies for all connected devices
- VPN Support Secure access to your home or office network from remote devices
- SPI and NAT Firewall Protects end-user devices from potential attacks from the Internet

Beamforming Technology For Laser-Focused Wi-Fi

Beamforming concentrates the Wi-Fi signal towards your devices, focusing the data transmission toward the most-needed directions. Superior Wi-Fi bandwidth utilization increases Wi-Fi range, delivering highly targeted and efficient Wi-Fi connections.



Versatile Connectivity

As a complete integrated modem router, the Archer VR900 provides versatile connectivity options including VDSL/ADSL, fiber/cable and 3G/4G USB dongle connections. This makes it easier when users need to choose among different Internet service providers when necessary.



Specifications

Hardware

 Ethernet Ports: 3 10/100/1000Mbps RJ45 LAN Ports, 1 10/100/1000Mbps RJ45 WAN/LAN Port, 1 RJ11 Port

• USB Ports: 2 USB 3.0 Ports

• Button: WPS Button, LED Button, Wireless On/Off Button, Power On/Off Button

External Power Supply: 12V/2.5A

• **Dimensions (W x D x H):** 8.5 x 6.5 x 1.5 in. (216 x 164 x 36.8mm)

• **IEEE Standards:** IEEE 802.3, IEEE 802.3u, 802.3ab

· VDSL2 Standards: ITU G.993.2, Up to 17a profile (POTS)

ITU-T G.993.5 (G.vector) ITU-T G.998.4 (G.INP)

· ADSL Standards: Full-rate ANSI T1.413 Issue 2,

ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs),

ITU-T G.995.1

· ADSL2 Standards: ITU-T G.992.3 (G.DMT.bis),

ITU-T G.992.4 (G.lite.bis)

• ADSL2+ Standards: ITU-T G.992.5

· Antenna Type: 3 external detachable dual band antennas (RP-SMA)

• Antenna Gain: 3 x 2dBi for 2.4GHz and 3 x 3dBi for 5GHz

Wireless

· Wireless Standards: IEEE 802.11a/n/ac 5GHz, IEEE 802.11b/g/n 2.4GHz

Frequency: 2.4GHz and 5GHz (Supports DFS)

· Signal Rate: 1300Mbps at 5GHz, 600Mbps at 2.4GHz

Transmit Power: <20dBm(EIRP)

 Wireless Function: Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics

 Wireless Security: 64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA-PSK2 encryptions, Wireless MAC Filtering

· Wireless Schedule: Support 2.4GHz and 5GHz Wireless Schedule





Specifications

Software

- Operation Modes: VDSL/ADSL Modem Router, Wireless Router, 3G/4G Router
- · DHCP: Server, Client, DHCP Client List, Address Reservation, DHCP Relay
- Quality of Service: ATM QoS, Traffic Control(IP QoS)
- · Port Forwarding: Virtual Server, Port Triggering, DMZ, ALG, UPnP
- · Dynamic DNS: DynDns, NO-IP
- · VPN Passthrough: PPTP, L2TP, IPSec Passthrough
- ATM/PPP Protocols: ATM Forum UNI3.1/4.0, PPP over ATM (RFC 2364), PPP over Ethernet (RFC2516), IPoA (RFC1577/2225), MER\IPoE (RFC 1483 Routed), Bridge (RFC1483 Bridge), PVC – Up to 8 PVCs
- Security: NAT Firewall, Access Control, MAC / IP / URL Filtering, Denial of Service (DoS), SYN Flooding, Ping of Death, IP and MAC Address Binding
- Advanced Functions: Parental Control, Network Address Translation(NAT), Port Mapping(Grouping), Static Routing, RIP v1/v2(optional), DNS Relay, DDNS, IGMP V1/V2/V3
- USB Sharing: Support Samba(Storage)/FTP Server/Media Server/Printer Server, 3G/4G Modem
- Management: Web Based Configuration(HTTP), Remote management, command Line Interface, SSL for TR-069, SNMP v1/2c, Web Based Firmware Upgrade, Diagnostic Tools, Free Online Firmware Update
- Guest Network: 2.4GHz guest network, 5GHz guest network
- · IPSec VPN: Supports up to 10 IPSec VPN tunnels
- · Protocols: Supports IPv4 and IPv6

Others

Package Contents

- · AC1900 Wireless Gigabit VDSL/ADSL Modem Router Archer VR900
- · External Splitter
- · RJ11 DSL Cable
- · RJ45 Ethernet Cable
- · Power Adapter
- · Quick Installation Guide

Certification

· CE, FCC, RCM, RoHS

System Requirements


- Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux
- · Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
- · Cable or DSL Modem
- · Subscription with an Internet Service Provider (for Internet access)


Environment

- · Operating Temperature: $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ (32 °F ~ 104 °F)
- Storage Temperature: $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (-40 °F ~158 °F)
- · Operating Humidity: 10%~90% non-condensing
- · Storage Humidity: 5%~90% non-condensing

Others

Ideal to use with





Similar Products











🗜 🗖 For more information, please visit

http://www.tp-link.com/en/products/details/?categoryid=&model=Archer+VR900

or scan the QR code left

Specifications are subject to change without notice. TP-LINK is a registered trademark of TP-LINK Technologies CO., Ltd. Other brands and product names are trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from TP-LINK Technologies CO., Ltd.

www.tp-link.com